

HYGROPALM HP31/HP32



HP31 with fixed probe

HP32 with HC2A probe

Benefits

- Measures relative humidity and temperature and perform psychrometric calculations
- Visual and audible alarms
- Graphic display for saved data
- 64'000 data points memory with programmable logging interval
- Long-life rechargeable battery (up to 48 hours at a logging interval of 30 seconds)

Applications

- Field inspection and spot checks in HVAC
- Building management systems
- Agriculture and food industry
- Pharmaceutical industry



TECHNICAL INFORMATION

Compatible with

- For HP 32: All HC2 and HC2A probes (except HC2-LDP)
- Free HygroSoft Software for configuration and data read out


Package content

- HygroPalm HP31 or HP32 (without probe)
- Soft case
- USB-C to USB-A cable (computer connection and battery charging)

General specifications		
Order code	HP31	HP32
Device type	Handheld device (%rh / °C)	
Compatible probes (HP32)	Fixed probe	All HC2A and HC2 probes (except HC2-LDP)
Application range	-10...60 °C 0...100 %rh (non-cond.)	
Storage range	-10...45 °C 10...90 %rh	
Probe application range	-10...60 °C 0...100 %rh (non-cond.)	Depends on probe
Functions	Spot measurements Programmable logging interval MIN / MAX / AVG	


General specifications		
Order code	HP31	HP32
Accuracy @ 23°C	±2 %rH / ±0.3 °C	Depends on probe
Logging interval	1 s...24 h	
Memory capacity	8 x 8000 data points	
Psychrometric calculations	Dew / Frost point (Dp / Fp) Wet bulb temperature (Tw) Enthalpy (H) Vapor concentration (Dv) Specific humidity (Q) Mixing ratio by weight (R) Vapor pressure (E) Saturation vapor pressure (Ew) Saturation vapor density (SVD)	
Calculation method	WMO Standard	
Display refresh rate	1 s (typical)	
Integrated battery	Lithium polymer, 3.7 V, 1000 mAh 48 h – Logging every 30 s, screen off 10 h – Screen always on	
PC interface	USB-C to USB-A, HygroSoft Software compatible	
Housing / Mechanics		
Enclosure material	ABS, TPR	
IP protection class	IP65	
Dimensions	160 x 63 x 30 mm	
Weight	185 g	

Dimensions HP31



Dimensions HP32

All HC2A and HC2 probes (except HC2-LDP)



POSSIBLE PROBES FOR THE HP32

Standard and High Precision probes

Accuracy (Standard):	$\pm 0.8\% \text{rh}$, $\pm 0.1 \text{ K}$ at 10...30 °C
Accuracy (High Precision):	$\pm 0.5\% \text{rh}$ at 10...90 %rh, $\pm 0.1 \text{ K}$ at 10...30 °C
Application range:	-50...100 °C, 0...100 %rh
Long-term stability:	< 1 %rh / year
Order code:	HC2A-S (Standard) HC2A-SH (High Precision)



High temperature handheld probe

Accuracy:	$\pm 0.8\% \text{rh}$, $\pm 0.2 \text{ K}$ at 10...30 °C
Application range:	-100...200 °C, 0...100 %rh
Long-term stability:	< 1 %rh / year
Cable length:	2 m
Order code:	HC2-HK25



Insertion probes

Accuracy:	$\pm 0.8/1.5\% \text{rh}$, $\pm 0.1/0.3 \text{ K}$ at 10...30 °C
Application range:	-40...85 °C / 0...100 %rh
Long-term stability:	< 1 %rh / year
Cable length:	2 m
Order code:	HC2-P05, HC2-P28, HC2-P50



HP32 PRODUCT SETS

HP32-S-SET

Consisting of:

- 1x HP32 handheld instrument
- 1x HC2A-S Standard probe

Order code: HP32-S-SET



HP32-SET

Consisting of:

- 1x HP32 handheld instrument
- 1x HC2A-S Standard probe
- 1x E2-02A extension cable 2 m
- 1x ER-15 calibration device
- 1x EA35-SCS humidity standard SCS

Order code: HP32-SET



HP32-A-REF-SET

Consisting of:

- 1x HP32 handheld instrument
- 1x HC2A-S Standard probe with 1x SCS-1T-3H
- 1x E2-02A extension cable 2 m

Order code: HP32-A-REF-SET



POSSIBLE SOFTWARE FOR THE HP32

HygroSoft software

- Free evaluation & configuration Software HygroSoft
- Visualization, data export and evaluation of measured values
- Handheld programming, data retrieval, scaling, Instrument settings, alarm function, service and configuration tool, time synchronization

An up-to-date overview of our extensive range of accessories such as probes, cables, filters, sets, software and calibration equipment compatible with the HygroPalm HP32 is available on our web site: